P/N: 10337SCE-BLK

Ratchet Tie Down

Hook and Keeper Reverse Action
50mm x 9m LC 2500kg, Hi-Visibility Strapping
Short Tail legth 500mm, BLACK Ratchet handle

SILVERBACK
SUPERIOR PROTECTION & SAFETY



NEW STRONGER LONG HANDLE REVERSE ACTION RATCHET

Experience reduced fatigue and enhanced safety with gravity-assisted ratcheting and robust 2500kg rated hooks.

New Stronger Long Handle Reverse Action Ratchet Tie Down Systems are a complete system ready to use. Each tie down comes with a black long handle reverse "ergo" ratchet buckle producing 500-530 daN, pre-tension, with moulded handle for extra comfort. The tail strap is fitted with a 2500kg rated hook and keeper for use on rails. The main strap is fitted with 2500kg rated hook and keeper, plus 2 protective Silverback wear sleeves.

The reverse action means tensioning is achieved when ratcheting in the downward direction and the assistance of gravity therefore reduces user fatigue, and arm, shoulder and back strain injuries. The longer tail length design places the ratchet buckle at an optimum position on most truck/ trailer heights to promote good posture and safe tensioning technique for the user. Silverback's standard action short handle 2500kg LC ratchet buckles achieve pre-tension of 400daN and the Silverback Long Handle Reverse Action achieves 500-530 daN, and that's more than most other brands of reverse action 2500kg LC ratchets available in Australia.

The Ratchet Tie-Down System works on semi-trailers, body trucks, utes, containers or anywhere you need to lash equipment down. Custom options available.

All our straps are designed, manufactured and tested for compliance with AS/NZS 4380:2001 and are backed by the Silverback assurance of quality. Compliance Tags are securely attached to the webbing.

SAFETY ADVICE & MAINTENANCE:

- We recommend frequent visual inspections of load restraints to ensure the quality and load restraining capability is not compromised.
- Keeping your ratchet tie downs in good working order will make them last longer and maintain their performance.
- Wipe webbing straps down with a dampened cloth to remove dirt and grime and use a small amount of dry lubricant on the moving parts of the ratchet buckle.
- Silverback ratchets are designed and tested for hand tensioning only. The use of any mechanical or other devices to tension ratchet tie downs could comprise the device, void any warranty claim and result in load restraint failure causing damage or injury.
- When load restraints are not in use consider using Silverback Strap winders to keep straps neatly rolled up when stored and ready for their next use.
- WARNING – Do Not use webbing straps with chemicals or extremely high temperatures.

IMPORTANT – Load Restraints are not to be used for lifting applications.

Scan for more info

1300 858 858 • online@silverback.com.au

ALBURY • MELBOURNE • BRISBANE • TOWNSVILLE • SYDNEY • ADELAIDE • PERTH

silverback.com.au