

P/N: 31951

Elite Single Leg Shock Absorbing Webbing Lanyard With Snap Hooks



AS/NZS 1891.1:2007
BMP 713822
BMP 713823
Australian Standard



PRODUCT DETAILS

- AUS/NZ designed and engineered.
- High Tenacity webbing 33kN, 220% over AS/NZS 1891.1 requirements.
- Contrast stitch thread colour for easy inspection.
- Standard LINQ shock absorber is rated for a wearer of up to 160kg, including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- Custom lengths available on request, for example, 1.0m, 1.2m, 1.5m, 1.8m
- Webbing Material: Polyester; 45mm; UV-Resilient; Solvent Resistant.
- Fall Arrest Hardware: Drop Forged corrosion-resistant electrophoresis; high-strength alloy steel.
- Stitch Pattern: THETA Pattern combines 423 stitches to exceed 33kN of strength; AS/NZ compliant colour contrast.
- Web Tenacity: Min 30kN Max 33kN.

Safety that Holds Every Time.

The LINQ 2 metre WLO1 Single Leg Webbing Lanyard with Snap Hooks is attached from the worker's safety harness to an anchor point on a building or structure to stop the worker from free-falling. It comes equipped with a shock-absorbing pack so that the forces on the user's body are reduced in the event of a fall.

FEATURES:

- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg, including tools and equipment.
- Drop forged lanyard hardware.
- Stitching patterns are sewn by computer-controlled bar tacking machinery for precision using UV-resistant high-tenacity polyester yarn with 100 newtons (10kg) breaking strength.
- The unique THETA stitch pattern has over 423 stitches resulting in a seam that matches the lanyard's webbing strength of 3.3t, ensuring no weak point in the lanyard assembly.



Scan for more info

1300 858 858 • online@silverback.com.au

MELBOURNE • BRISBANE • TOWNSVILLE • SYDNEY • ADELAIDE • PERTH

silverback.com.au